Professional Marksman Series RIFLE TELESCOPE 3-15x50mm Model TT315P

Tangent Theta 3-15x50mm model TT315P Rifle Telescope is a long-range precision sighting instrument for professional marksmen. Designed for heavy field use, Tangent Theta's industry-leading development team has used their extensive experience to optimize and refine it for unfailing ruggedness, mechanical precision and unsurpassed image quality. Elevation and windage mechanisms exhibit precise tactile response and feature a truly tool-less re-zero procedure.

Tangent Theta rifle telescopes are built in Canada and are specifically designed and function-tested for long lifecycles in the harshest of environmental conditions.

50mm objective lens 34mm main tube eleven reticle illumination settings side parallax adjustment tool-less re-zero feature (patent pending) non-translating knobs with elevation zero-stop double-turn elevation with revolution indicator 3-15x magnification range lockable rapid adjusting diopter

3 R

ANGENTOTHE

Professional Marksman Series RIFLE TELESCOPE 3-15x50mm Model TT315P



Professional Marksman Series RIFLE TELESCOPE 3-15x50mm Model TT315P

SPECIFICATIONS*

Magnification —		3x-15x
Length		
Width		103mm
Height		82mm
Weight		1025g
Tube diameter —		
Objective bell diam	ieter ———	57mm
Objective lens diar		
Eyepiece diameter		45mm
Reticle options —		Gen 2, Gen 2XR, MoA
		7.3 degrees (12.8m @ 100m)
Field of View @ 15	κ	1.6 degrees (2.8m @ 100m)
Diopter range		-3 to +2.5
Eve relief		90mm
Exit pupil @ 3x —		11.5mm
Exit pupil @ 15x –		3.5mm
Re-zero mechanisi	n	tool-less re-zero (patent pendin
Total Adjustment R	ange	
		34 mrad (117 MoA)
Windage -		+/- 8 mrad (+/- 27 MoA)
Working Adjustmer	nt Range	
Elevation -		28 mrad /96 MoA
Windage -		+/- 6 mrad (+/- 20.5 MoA)
		0.1 mrad or 1/4 MoA
Parallax adjustmen	t range ———	50m to infinity
Crosshair illuminati		
		DL2032 3v lithium
Exterior finish —		Type II Anodized, matte
Environmental		
Waterproof		4 hours @ 10 meters
Shockproot		700g's @ 10,000 cycles
Standard accesso	ries ———	Tenebraex [®] lens covers & ARD

ero (patent pending) 7 MoA) /- 27 MoA) MoA /- 20.5 MoA) /4 MoA



www.armament.com sales@armament.com

5P -3 -15x50mm Model \mathfrak{O} 5 Ζ

* Subject to change. Consult www.tangenttheta.com for current specifications.